




## Compact Tel/Fax/Modem/ADSL protection!



Photo not binding

The ideal and compact surge protector dedicated to the protection of your phone line as well as your home equipment.

- Type 3 surge protector
- 1 surge protected outlet shuko type
- Active protection LED
- Tel/fax/modem/ADSL line protection
- EMI/RFI noise filter
- Child-proof safety shutters
- Up to 25.000€ insurance for connected equipment (see terms and conditions on the web site: [www.infosec-ups.com](http://www.infosec-ups.com))



### Trick & tip:

Connect your old power strip to PFS TEL1 and convert it into a surge suppressor.

General specifications	
1 protected outlet	
Non-flammable plastic housing & child-proof safety shutters	
Dimensions (hwxwd) mm : 102 x 70 x 36	
weight : 150 g	
German type outlet	
Conform with CE standard	
Lifetime warranty	
Electrical specifications	
Nominal Voltage	250 VAC
Clamping voltage	775 V
Maximum power	16 A / 3520 Watts
Surge energy rating	714 Joules (H-N, H-G, N-G)
Peak current 8/20 μs	19 500 A ( 6 500 A x 3 lines)
Response time	<1 nanosecond
EMI/RFI filter	
Frequency range	150 KHz ~ 100 MHz
Attenuation	Up to 40 dB
Tel/fax/modem line protection	
Jacks	1 RJ11 in + 1 RJ11 out (6P4C)
Clamping voltage	395 V
Energy	320 joules
Environment	
Temperature	0 to 40 °c
Relative humidity	0 to 95 %



**Infosec Communication**  
4, rue de la Rigotière  
44700 ORVAULT  
France

**Contact Commercial:**  
Tél : +33 2 40 76 11 77  
commercial@infosec.fr

[www.infosec-ups.com](http://www.infosec-ups.com)

GB 30 05 08